

ECO 1 DIGITAL PRESSURE GAUGE ACURACY 1% WITH MIN AND MAX. FUNCTION

ECO1 is a compact and economic digital pressure measuring instrument. It is of medium accuracy, but of high resolution and repeatability.

The pressure is measured twice per second and displayed. The top display indicates the actual pressure, the bottom display shows the MAX.- or MIN.- pressure since the last RESET.

ECO1 has two operating keys. The left key is to turn the instrument on and to execute its functions (the functions appear successively on the display as long as the key is pressed and are executed when releasing the key). The right key is also used to switch between the MAX.- and MIN.- value.

The instrument has the following functions:

RESET : With the RESET-functions, the MAX.- and MIN.- value is set to the actual pressure value.

OFF: Turns off the instrument.

ZERO: The ZERO-function allows to set any value as a new Zero reference. Barometric pressure variations can be thus be compensated. The factory setting of the Zero for the range $-1...30$ bar is at 0 bar absolute. For sealed gauge pressure measurements, activate "ZERO SET" at ambient pressure.

Instruments with the range $0...300$ bar are calibrated in a sealed gauge mode with 1 bar absolute pressure as a Zero reference.

CONT: The instrument turns of 15 Min. After the last key function. Activating CONT (Continuous) deactivates this automatic turn-off.

ECO 1 has 7/16" UNF male thread and is delivered complete with an O-ring seal swivel fitting which allows ECO 1 to be rotated through 360°. Only minimal tightness is needed to seal up to 300 bar. Process pressure connection is G 1/4 " male.



SPECIFICATIONS:

Ranges:	-1...30 bar	0...300 bar
Resolution:	10 mbar	100 mbar
Accuracy:	0,5% FS type. (1% FE max.)	
Storage/ Operating temperature:	-30...80°C / 0...50°C	
Compensated temperature range:	0...50°C	
Supply:	3V battery, type CR 2430	
Battery life:	1400 hours continuous operation	
Pressure connection:	7/16"-20UNF (adapter G1/4" included)	
Protection, CEI 529:	IP65	
Diameter x Height x Depth:	59x95x32 mm	
Weight:	≈125 g	

The EEx is a version of ECO 1 incorporates an additional protection switch. Functions, ranges and accuracy are identical to the standard version.

This publication does not try to establish the bases of a contract and the company keeps the right to modify without previous notice the design and the specifications of the instruments, in accordance with his politics of continued development.